


MAI[®] 2PUMPTAURUS



THE INDIVIDUAL IS OUR MAIN CONCERN

... IT DOESN'T GET ANY BETTER

MAI[®] 2PUMPTAURUS

FULL SPEED AHEAD

- The greatest possible flexibility when changing location from the 1st to the 6th floor, from the 6th to the 12 floor, etc.
 - Generous conveying distances

SAVE TIME AND MONEY

The variable conveying capacity will increase efficiency at construction sites, because time-consuming retooling has been made unnecessary. No more rights of recourse from the builder because of corrosion or paint residue on the facade. We guarantee it!

THE ADVANTAGES AT A GLANCE

- Robust construction for the toughest uses
 - Reliable and low-cost operation
- Modular construction guarantees suitability for all performance ranges

IT CAN ALSO OFFER

- Small but powerfull
 - Extreme ease of operation
- Stainless steel guarantees freedom from corrosion

TECHNISCHE DATEN

Operating voltage:	400V/3/PE/50Hz
Nominal power:	7,5 kW
Fusing:	32 A
Feed capacity:	5 - 150 l/min
L x W x H:	136 x 82 x 76 cm
Filling height:	76 cm
Total weight:	230 kg



MAI[®] International GmbH, Werkstraße 17, 9710 Feistritz/Drau
Austria, Europe, E-mail: mai@mai.at, Internet: www.mai.at
Tel. +43 4245/6233 0, Fax +43 4245/6233 10

MAI[®] and MAI-PUMP[®] are registered trademarks of MAI[®] International GmbH.
MAI[®] International GmbH reserves the right to alter its machine specifications and descriptions at any time without prior notice. © MAI[®] International GmbH, 2020, EN07

MAI
INTERNATIONAL[®]